

## COMPRESSION MOULDING PRESS

Model No.  
**K-CMP-01**



### Description

**Kant Plastology** is dedicatedly involved in offering wide array of **COMPRESSION MOULDING PRESS**. The product is manufactured by using optimum grade raw material and latest technology at our state of art manufacturing unit. The rigid structure with elegant look is basic features of the floor mounting machine. The product has good temperature accuracy due to using of micro processor based double display digital PID controller.

### Specification

MODEL (K-CMP-01)	
Press Capacity	20 T / 40 T / 60 T / 100 T
System Status	Digital
Temperature Controller	Micro processor based double display digital PID controller
Temperature Range	Ambient to 200°C
Timer	Micro processor based double display digital timer with Hooter
Timer Range / Resolution	Up to 999.59 min. / 1 sec.
Insulation	Heat insulator in form of Teflon sheet inserted between heating & cooling plates
Ram Movement	Down acting
Distance Between Tie Bars	Distance between tie bars is 260mm or optional
Motor	1.5kW
Ram Closing Speed	3.5mm/sec.
Ram Opening Speed	5mm/sec.
Max. Daylight	250mm or optional
Min. Daylight	50mm
Max. Stroke Size	200mm or optional
Power Supply	440V AC, Three phase, 50Hz